

Dimensions & Specifications

Model	Product #	Volts	Amps	Tank Heater Watts	Total Watts	Brewing Capacity	Cu. Ft.	Shipping Weight	Cord Attached
CWTF15-2	12950.0211	120	15	1320	1800	3.8 gal./hr.	3.85	30 lbs. (13.6 kg)	Yes
CWTF15-3	12950.0213	120	15	1320	1800	3.8 gal./hr.	3.85	31 lbs. (14.1 kg)	Yes
CWTF15-3	12950.0217	120	15	1320	1800	3.8 gal./hr.	3.85	32 lbs. (14.5 kg)	Yes
CWTF20-3	12950.0283	120	20	1800	2400	5.1 gal./hr.	3.98	31 lbs. (14.1 kg)	No
CWTF35-3	12950.0253	120/240	19.6	3500	4100	6.8 gal./hr.	3.9	30 lbs. (13.6 kg)	No
CWTF35-3	12950.0261	120/240	19.6	3500	4100	6.8 gal./hr.	3.85	32 lbs. (14.5 kg)	No

Electrical: Model 15 requires 2-wires plus ground service rated 120V, single phase, 60 Hz.

Model 20 requires 2-wires plus ground service rated 120V, single phase, 60 Hz.

Model 35 requires 3-wires plus ground service rated 120/208 or 120/240V, single phase, 60 Hz.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with 1/4" male flare fitting.

